
For Safety –

- 1. Operate only with the instructor's permission and after you have received instruction
- 2. Remove jewelry, eliminate loose clothing, and confine long hair
- 3. Make sure all guards are in place and operating correctly
- 4. Always wear proper eye protection
- 5. The tool rests must be adjusted to as close as possible, but not exceeding, $\frac{1}{16}$ in. of the grinding wheel
- 6. Spark deflectors must be adjusted to as close as possible, but not exceeding, $\frac{1}{16}$ in. of the grinding wheel
- 7. Do not grind on the side of the grinding wheel
- 8. Stand to one side when starting the machine
- 9. Discard or report grinding wheels that are excessively small or cracked
- 10. Small work pieces should be held with vise grip-type pliers
- 11. Do not leave the machine until the grinding wheels have come to a full stop

Pedestal Grinder




Name:			0 10 Te -	
Date:				
AM / PM	Year.	1	2	

Safety Quiz

Circle One 1. The tool rest should be adjusted to within True | False $\frac{1}{2}$ in. of the wheel 2. Eye protection is always necessary when True | False grinding 3. Once the off switch is in the off position, True | False the operator may leave 4. Wheels that are slightly cracked may be True | False used 5. The spark arrestor is not necessary if there True | False is a safety shield 6. When grinding a small piece of steel, vise True | False grips are advised

Pedestal Grinder



Word Bank

Power Switch
Wheel Guard
Dust Chute
Pedestal
Tool Rest
Spark Deflector
Wheel
Safety Shield
Water Pot

Pedestal Grinder